



Standard Recovery Diode, 35A

Features

- Glass passivated die
- Low forward voltage drop
- High surge capability
- Low leakage current
- Normal and Reverse polarity
- Metric and UNF threads available



DO-203AB (DO-5)

Maximum Ratings ($T_J = 25^\circ\text{C}$, unless otherwise noted)							
Parameter	Test Conditions	Symbol	1N3765(R)	1N3766(R)	1N3767(R)	1N3768(R)	Units
Repetitive peak reverse voltage		V_{RRM}	700	800	900	1000	V
RMS reverse voltage		V_{RMS}	490	560	630	700	V
DC blocking voltage		V_{DC}	700	800	900	1000	V
Continuous forward current	$T_C \leq 140^\circ\text{C}$	$I_{F(AV)}$	35	35	35	35	A
Surge non-repetitive forward current, half-sine wave	$T_C = 25^\circ\text{C}$	I_{FSM}	475	475	475	475	A
Maximum peak forward voltage	$T_J = 25^\circ\text{C}$	V_F	1.2	1.2	1.2	1.2	V
Reverse current	$T_J = 25^\circ\text{C}$	I_R	10	10	10	10	μA
	$T_J = 140^\circ\text{C}$		10	10	10	10	mA

Thermal & Mechanical Specifications ($T_J = 25^\circ\text{C}$, unless otherwise noted)						
Parameters	Symbol	1N3765(R)	1N3766(R)	1N3767(R)	1N3768(R)	Units
Thermal resistance, junction to case	$R_{th(jc)}$	0.25	0.25	0.25	0.25	$^\circ\text{C}/\text{W}$
Operating junction temperature range	T_J	-55 to 160	-55 to 160	-55 to 160	-55 to 160	$^\circ\text{C}$
Storage temperature	T_{stg}	-55 to 160	-55 to 160	-55 to 160	-55 to 160	$^\circ\text{C}$
Mounting torque, non-lubricated threads, tightening on nut	F	3.4 \pm 10%				Nm
Approximate weight	W	16				g

Package Outline

Dimensions for DO-203AB (DO-5) (in millimeters)

