

Produktübersicht ULTRACAP Kleinzellen Fab. SAMWHA

CapComp GmbH - Gründelbachstr. 10 - D-71691 Freiberg/Neckar

www.capcomp.de - shop24.capcomp.de - Tel: +49 7141 298950

Stand 01.06.2023



Series	Part Number	Voltage (V)	Capacity (F)	ESR (mΩ)		LC (mA) (RT 72hrs)	Rated Current (A) 15/40°C	Peak Current (A)	Max Energy Stored (Wh)	Max Energy Density (Wh/Kg)	Weight (g)	Packaging (pcs) bulk/carton	Dimension (mm)			
				AC@(1kHz)	DC								D+1	L±1	P±0,5	d±0.05
DS Radial	DSSU305W08020BB	2.7	3	50	80	0,007		3,3	0,003	2,17	1,4		8	20	3,5	0,6
	DSSU505W10020BB	2.7	5	45	60	0,010		5,2	0,005	2,41	2,1		10	20	5,0	0,6
	DSSU106W10030BB	2.7	10	25	45	0,023		9,3	0,01	3,49	2,9	1200/4800	10	30	5,0	0,6
	DSSU156W12025BB	2.7	15	20	40	0,030		12,7	0,015	3,38	4,5		12,5	25		
	DSSU256W16025BB	2.7	25	15	25	0,045		20,8	0,025	3,78	6,7	500/2000	16	25	7,5	0,8
	DSSU336W18032BB	2.7	33	11	20	0,060		26,8	0,033	3,34	10,0		18	32	7,5	0,8
	DSSU506W18040BB	2.7	50	9	15	0,075		38,6	0,051	4,4	11,5	300/1200	18	40	7,5	0,8
DSSU107W22045BB	2.7	100	8	13	0,180		58,7	0,101	4,82	21,0		22	45			
DS Radial	DSOU305W08020BB	3,0	3	60	105	0,010		3,4	0,004	2,34	1,6		8	20	3,5	0,6
	DSOU505W10020BB	3,0	5	50	90	0,015		5,2	0,006	2,84	2,2		10	20	5,0	0,6
	DSOU106W10030BB	3,0	10	30	45	0,030		10,3	0,013	3,57	3,5	1200/4800	10	30	5,0	0,6
	DSOU156W12025BB	3,0	15	25	40	0,050		14,1	0,019	4,17	4,5		12,5	25		
	DSOU256W16025BB	3,0	25	20	30	0,070		21,4	0,031	4,17	7,5	500/2000	16	25	7,5	0,8
DSOU506W18040BB	3,0	50	10	20	0,150		37,5	0,063	4,53	13,8	300/1200	18	40	7,5	0,8	

